

## KEMCRYL 901/ PRIMCRYL WATER BASED ACRYLIC PRIMER

Rev.00-241110

PRODUCT DESCRIPTION	
<p>PrimCryl primer is a water based one-component acrylic primer. It is designed to use on concrete masonry substrate primer to application of KemCryl 911, KemAqua Guard 811. KemCryl 901 primer reduces uneven absorption rate and provides excellent key for over coating with KemCryl 911, KemAqua Guard 811, and KemThane 812.</p>	
INTENDED USES	
<p>Interior &amp; Exterior painting for building.</p>	
SPECIFICATION DATA	
<b>Thickness</b>	30 micron
<b>Type</b>	1 pack
<b>Shade</b>	White
<b>Finish</b>	Matt
<b>Chemical Base</b>	Styrene Acrylic Based
<b>Mixing Ratio</b>	N/A
<b>Coverage m<sup>2</sup>/ltr.</b>	7.5
<b>Recommended No. Of Coats</b>	1
<b>Re-coating Interval</b>	5 hrs
<b>Surface Dry Time</b>	1 hr
<b>Curing Time</b>	16 hrs
<b>Pot Life</b>	N/A
<b>Shelf Life (under std. condition)</b>	6 months
<b>Recommended System</b>	Primer
<b>Pack Size</b>	20 L
<p><b>Note:</b> These figures are theoretical under controlled conditions and may vary depending upon site conditions i.e. temp., humidity, surface porosity, surface profile, handling of material etc.</p>	
DIRECTION OF USE	
<p><b>SURFACE PREPARATION:</b></p> <p>The new concrete surface should be allowed to cure for 28 days. Concrete surface should be thoroughly cleaned to remove all loose particles and old paint if any. Surface should be leveled properly using suitable putty.</p> <p><b>PRIMCRYL APPLICATION:</b></p> <p>Ensure substrate is clean and free from grease and foreign material. Apply KemCryl 901 primer to clean dry</p>	

## KEMCRYL 901/ PRIMCRYL WATER BASED ACRYLIC PRIMER

Rev.00-241110

<p>surface using roller brush or spray. It can be applied to very slightly damp surfaces. Primer can be thinned up to 20% with water. Use brush/ roller.</p>	
<p><b>CLEAN UP</b></p>	
<p>For cleaning of application equipment and tools use water.</p>	
<p><b>MAINTENANCE</b></p>	<p><b>SAFETY PRECATIONS</b></p>
<p>For maximum life expectancy, routinely sweep and wash floors with conventional detergent cleaners. Do not steam clean: all spills powder or liquid should be cleaned up immediately. Inspect the floor regularly for wear, breaks or damages, if found any immediately consult with Chembond's technical service personnel or authorized applicator.</p>	<p>Take care to avoid skin or eye contact and breathing vapours. In the event of the skin contact immediately wash thoroughly. In the event of eye contact, wash continuously for 15 minutes in water and seek medical advice. Wear protective clothing, gloves, and safety glasses while using this product. If inhalation occurs, move to fresh air and seek medical advice in case of difficulty in breathing. Keep material away from heat, flames, and sources of ignition. For further details read Material Safety Data Sheet.</p>
<p><b>LIMITATIONS OF LIABILITY</b></p>	
<p>This information is based on our current level of knowledge. It is given in a good faith but it is not intended to guarantee any particular properties. The users must satisfy themselves that there are no circumstances requiring additional information or precautions or the verification of details given herein.</p>	



### Chembond Chemicals Limited

Chembond Centre  
EL-71, MIDC Mahape,  
Navi Mumbai 400 710  
INDIA

Tel: (91 22) 66143000 / 315  
Fax: (91 22) 768 1294  
E-mail: sales@chembondcoatings.com  
Website: www.chembondindia.com